



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification⁶ :

H04B 7/005, H04Q 7/20, 7/34

A1

(11) International Publication Number:

WO 99/55018

(43) International Publication Date:

28 October 1999 (28.10.99)

(21) International Application Number: PCT/US99/08657

(22) International Filing Date: 20 April 1999 (20.04.99)

(30) Priority Data:

60/082,527	21 April 1998 (21.04.98)	US
09/290,589	13 April 1999 (13.04.99)	US

(71) Applicant: MOTOROLA INC. [US/US]; 1303 East Algonquin Road, Schaumburg, IL 60196 (US).


(72) Inventor: VANDERSPOOL, Jan, P., II; 8708 Bull Run Trail, Woodstock, IL 60098 (US).

(74) Agents: HAAS, Kenneth, A. et al.; Motorola Inc., Intellectual Property Dept., 1303 East Algonquin Road, Schaumburg, IL 60196 (US).

(81) Designated States: European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published*With international search report.**Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.*

(54) Title: A METHOD FOR LOCATING A REMOTE UNIT WITHIN A COMMUNICATION SYSTEM

**(57) Abstract**

Base stations (101-105) transmit, and a remote unit (117) receives a radio frequency (RF) location signal. The remote unit (113) then computes an observed-time-difference (OTD) for each base station at particular time t_1 . Observed differences in received signal times, and are reported to a Mobile Location Center (MLC) (111). Additionally, a Real-Time-Difference receiver (115) receives an RF signal from two or more base stations. The Real Time Differences between the base stations (101-105) are computed at a second time. These differences are also reported to the MLC (111). The MLC (111) computes an estimated RTD for the time period t_1 via standard curve fitting algorithms, or simple interpolating algorithms. A corrected Time Difference of Arrival (TDOA) as determined by the remote unit (117) is computed based on the OTD measurements and the estimated RTD measurements.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

A METHOD FOR LOCATING A REMOTE UNIT WITHIN A COMMUNICATION SYSTEM

5

Field of the Invention

The present invention relates generally to cellular communication systems and, in particular, to a method and apparatus for locating a remote unit within such communication systems.

10

Background of the Invention

Radio location techniques that utilize a signal's Time Difference of Arrival (TDOA) have been widely used in many mobile transmitter location systems. The technique utilizes the propagation delay of the radio signal to infer the geographic distance. Three or more propagation delay measurements allow location computation. TDOA techniques can be applied to either the uplink signals received by the base stations from the mobile or the downlink signals transmitted from the base stations received by the mobiles. The use of uplink signals for location computation is commonly referred to as Time of Arrival (TOA). For the TOA case the mobile originates a signal having a single clock reference (the mobile's clock) and the base stations must measure the receive time using a sufficiently accurate multiple clocks. The use of downlink signals is commonly referred to as Enhanced Observed Time Difference (OTD). For the OTD case the base stations must have a sufficiently accurate known start time and the mobile provides the receive time measured against a single clock reference. Three or more base stations are used for either the TOA or OTD methods.

Both the TOA and OTD methods share an aspect of geometry having a three to one ratio as well as one end of the measurement being at known location(s). For the TOA method, a signal originating from a single mobile is measured by three or more geographically known measurement locations. For the OTD method, signals originating from three or more geographically dispersed signal sources (base stations at known locations) are measured by a single receiver (mobile). Due to the single end aspect of one end of the measurement combined

with the known location(s) at one end of the measurement, for the purpose of location computation, it is simply an algebraic manipulation as to whether the propagation delay measurements are considered as three or more individual propagation delay numbers or two or more time-differences.

5 The end of the measurement at the geographically disbursed locations (e.g., base stations) require the utilization of a reference clock ("internal clock") with a rate sufficiently accurate to limit the amount of error introduced by any time drift. Rather than synchronize all locations to a common clock reference such as GPS or to use highly stable clocks at all locations, it is accepted practice
10 to allow timing errors at the base stations. The errors are measured by a receiver device. This Real Time Difference (RTD) receiver reports the time differences referenced to a sufficiently stable internal clock. The TOA or OTD data and the RTD data is sent to a single computation location. These measurement and data collection processes (TOA/OTD data vs. RTD data and location computation) are
15 asynchronous and may be made at different points in time. When TOA or OTD data measured at time t_1 are used with RTD data measured at time t_2 , the actual RTD at t_1 is not known and the computation is in error by that amount. For accurate location calculations, there is a need to provide a method whereby this error can be removed while allowing the measurement processes to remain
20 asynchronous.

Brief Description of the Drawings

25 FIG. 1 is a block diagram showing a communication system in accordance with the preferred embodiment of the present invention.

FIG. 2 illustrates Real Time Difference (RTD) as a function of time for the communication system of FIG. 1.

FIG. 3 is a flow chart showing the operation of the communication system
30 of FIG. 1 in accordance with the preferred embodiment of the present invention.

Detailed Description of the Drawings

To overcome the problems described above, base stations transmit, and a remote unit receives a radio frequency (RF) location signal. The remote unit then computes an observed-time-difference (OTD) for each base station at particular time t_1 . The remote unit also time stamps each base station measured based on the air interface TDMA structure. (In the preferred embodiment for GSM, the frame number is used.) Observed differences in received signal times plus time stamps are reported to a Mobile Location Center (MLC). Additionally, a Real-Time-Difference receiver receives an RF signal from two or more base stations. The Real Time Differences between the base stations are computed at a separate time t_2 differing from time t_1 . The RTD receiver also time stamps measurements based on the air interface TDMA structure. These differences are also reported to the MLC and are acted upon (a computation is made) at time t_3 occurring after time t_1 and t_2 . In the preferred embodiment, historical raw data is retained at the MLC for a sufficient time to allow curve fitting. The MLC computes an estimated RTD at the time period t_1 via standard curve fitting algorithms, or simple interpolating or extrapolating algorithms. Alternatively, the curve fit data is available from any appropriate part of the location measurement system. A corrected Time Difference of Arrival (TDOA) as determined by the remote unit is computed based on the OTD measurements and the curve-fit RTD measurements.

Because RTD data utilized in calculating TDOA measurements is predicted RTD data at the time period when OTD data was taken by the remote unit, a more accurate measurement of location can be performed by the MLC. More particularly, prior-art procedures of locating a remote unit utilized the RTD data that was obtained at time period t_2 differing from t_1 in the calculation of the remote unit's location. Unlike the prior art methods of calculating location, a more accurate method for calculating location is utilized that predicts the RTD data for time period t_1 . This leads to location estimates having a greater accuracy than with prior-art location techniques.

The present invention encompasses a method for locating a remote unit within a communication system. The method comprises the steps of receiving a plurality of measurements from a remote unit of OTDs for a plurality of base stations, and receiving a measurement of RTD for the plurality of base stations performed at a second time period. In the preferred embodiment of the present invention the plurality of OTD measurements were performed at a first time period. A predicted RTD is calculated for the plurality of base stations at the first

time period, and a location is calculated for the remote unit based on the OTD measurements and the predicted RTD for the plurality of base stations at the first time period.

5 The present invention additionally encompasses a method for locating a remote unit within a communication system. The method comprises the steps of receiving a radio-frequency (RF) location signal transmitted via a downlink signal, computing an observed-time-difference OTD for each base station at a first time period, and computing a time period when the location signal was received. Thee OTD measurement is reported to infrastructure equipment (along with the
10 time period) for locating the remote unit.

Finally, the present invention encompasses a method for locating a remote unit within a communication system. The method comprises the steps of receiving a request to locate the remote unit, sending a downlink location signal to the remote unit, and performing a series of OTD measurements to obtain OTD
15 data at a first time period. RTD measurements for a plurality of base stations are obtained at a second time period. The OTD and RTD measurements are reported to a location center along the first and the second time period, and an RDT measurement a the third time period is predicted based on the RTD measurements. Finally, the remote unit is located based on the predicted RTD measurement and
20 the OTD measurements.

Turning now to the drawings, where like numerals designate like components, FIG. 1 is a block diagram showing a communication system 100 in accordance with the preferred embodiment of the present invention. In the preferred embodiment of the present invention, communication system 100
25 utilizes a Global System for Mobile Communications (GSM) protocol, but in alternate embodiments communication system 100 may utilize other analog or digital cellular communication system protocols such as, but not limited to, the Code Division Multiple Access (CDMA) system protocol as described in Cellular System Remote unit-Base Station Compatibility Standard of the Electronic
30 Industry Association/Telecommunications Industry Association Interim Standard 95 (TIA/EIA/IS-95A), the Narrowband Advanced Mobile Phone Service (NAMPS) protocol, the Advanced Mobile Phone Service (AMPS) protocol, the Personal Digital Cellular (PDC) protocol, or the United States Digital Cellular (USDC) protocol.

Communication system 100 includes Base Transceiver Stations (BTSS) 101-105, remote unit 117, Real-Time-Difference (RTD) receiver 115, Centralized Base Station Controller (CBSC) 107, Mobile Switching Center (MSC) 109, and Mobile Location Center (MLC) 111. In the preferred embodiment of the present invention base stations 101-105 are preferably Motorola base stations, MSC 104 is preferably a Motorola MSC, and CBSC 103 is preferably comprised of a Motorola CBSC component. As shown, remote unit 117 is receiving communication from base stations 101-105. Base stations 101-105 are suitably coupled to CBSC 107 and communicate to remote unit 117 via downlink communication signals 116. Although RTD receiver 115 is shown existing as a separate entity, in alternate embodiments of the present invention, RTD receiver may be combined with other network elements (e.g., MSC 109, MLC 111, . . . , etc.).

Operation of communication system 100 occurs as follows: To initiate a location request, a command is originated at a regional entity such as MSC 109, MLC 111, or perhaps within a connected network such as Public Switched Telephone Network (PSTN) (not shown). The location request, which includes identification information on the remote unit that is to be located enters HLR 113 where it is processed to determine the currently serving base station. Once the currently serving base station (e.g., base station 101) is known, the location request is passed to the appropriate base stations (e.g., neighboring base stations 103-105) and remote unit 117. Base stations 101-105 transmit, and remote unit 117 receives a radio frequency (RF) location signal transmitted via downlink signal 116. Remote unit 113 then computes an observed-time-difference (OTD) for each base station at particular time t_1 . Observed differences in received signal times (i.e., $(B-A)_{OTD}$ and $(B-C)_{OTD}$) are reported to the serving base station and ultimately to MLC 111. Additionally, the remote unit calculates and reports a time of the measurement relative to the TDMA air interface structure (reported as the frame number) for the measurement. In the preferred embodiment of the present invention the frame number corresponds to a time period when the downlink location signal was received.

In the preferred embodiment of the present invention RTD receiver 115 receives downlink RF signal 116 from two or more base stations. The Real Time Differences between base stations 101-105 are computed at time t_2 . These differences $(B-A)_{RTD}$ and $(B-C)_{RTD}$ as seen by receiver 115 are also reported to MLC 111. Additionally, the time of the measurement relative to the TDMA air

interface structure is reported as the frame number for the measurement. MLC 111 computes an estimated RTD for the time period t_1 via standard curve fitting algorithms, or simple interpolating algorithms. More particularly, a series of RTD measurements is taken by RTD receiver 115. Since RTD receiver is stationary, in theory, all RTD measurements for a particular combination of base stations due to propagation delay should be static. Since a base stations internal clock may be drifting with respect to time, RTD measurements, in reality, may not be static, and may vary with respect to time. MLC 111 utilizes information on how a particular RTD measurement for a combination of base stations varies with respect to time to produce an estimated RTD value for the time period t_1 . A corrected TDOA as determined by remote unit 117 is computed according to the equations:

$$\begin{aligned} \text{TDOA(B-A)} &= (\text{B-A})_{\text{OTD}} - (\text{B-A})_{\text{RTD}}(t_1), \text{ and} \\ \text{TDOA(B-C)} &= (\text{B-C})_{\text{OTD}} - (\text{B-C})_{\text{RTD}}(t_1), \end{aligned}$$

15

and where $(\text{B-A})_{\text{RTD}}(t_1)$ and $(\text{B-C})_{\text{RTD}}(t_1)$ are estimates of RTD data at time t_1 . The TDOA data is then placed into known location calculation equations to compute the location or remote unit 117.

In general, the error due to not using RTD data from coincident points in time with the OTD data may be significant compared to the desired location accuracy. This fact is illustrated in FIG. 2. In FIG. 2 RTD amounts for base stations 101-105 are illustrated by lines 201-205, respectively. As is evident, RTD data for all base stations 101-105 is a function of time. More particularly, RTD for base stations 103-105 has a positive slope indicating the time is advancing due to internal clocks that are fast. Similarly, RTD for base station 101 has a negative slope indicating the time is regressing due to an internal clock that is running slow.

Because RTD data utilized in calculating TDOA measurements is predicted RTD data at the time period when OTD data was taken by remote unit 117, a more accurate measurement of location can be performed by MLC 111. More particularly, prior-art procedures of locating remote unit 117 utilized the RTD data that was obtained at time period t_2 in the calculation of the remote unit's location. Unlike the prior art methods of calculating location, a more accurate method for calculating location is utilized that predicts the RTD data for

time period t_1 . This leads to location estimates having a greater accuracy than with prior-art location techniques.

In order for MLC 111 to accurately predict location estimates in accordance with the preferred embodiment of the present invention the time period t_1 needs to be provided to MLC 111. In the preferred embodiment of the present invention this is accomplished by remote unit 117 reporting a frame number along with OTD data to the serving base station. The frame number corresponds to a time period when OTD data was collected by remote unit 117. If OTD data is taken by a remote unit for several base stations, over a several-frame time period, then the frame number associated with a time period between the earliest and the latest OTD measurements is reported as the time period (t_1) when OTD data was obtained.

FIG. 3 is a flow chart showing the operation of communication system 100 in accordance with the preferred embodiment of the present invention. The logic flow begins at step 301 where remote unit 117, and base stations 101-105 receive a request to locate remote unit 117. At step 303 base stations 101-105 send downlink location signal (via downlink communication signal 116) to remote unit. At step 305, remote unit 117 performs a series of OTD measurements to obtain OTD data at a first time period. Next, at step 307 RTD receiver 115 obtains RTD measurements for base stations 101-105 and reports the measurements to the serving base station. In the preferred embodiment of the present invention step 307 is performed periodically by RDT receiver 115, regardless of whether location of remote unit 117 is desired. For example, in the preferred embodiment of the present invention RDT receiver takes, and reports RTD measurements every 30 seconds, regardless of whether location estimates are taking place.

Continuing, at step 309 the OTD and RTD measurements are received by MLC 111, and at step 311 a prediction of RTD measurements for the plurality of base stations at the first time period is made. Finally, at step 313 an estimated location of the remote unit is made based on the OTD measurements and the predicted RTD for the plurality of base stations at the first time period.

While the invention has been particularly shown and described with reference to a particular embodiment, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the spirit and scope of the invention. For example, the point of computation where the required location data converges for the final calculation may be in the

mobile (RU) rather than the MLC. The application of a curve fit algorithm to the RTD data may be in the MCL and delivered to the mobile. Alternatively, the application of a curve fit algorithm to the RTD may be done in the RTD and delivered to the MLC. The number of terms used in the curve fit algorithm (the
5 order of the fit) may vary and be within control of various elements within the location system allowing for multiple solutions to the curve-fit task. The use of frame number in a GSM system could be modified to any higher or lower modulo of the air interface to provide a sufficient accuracy for the intended computational accuracy. The juxtaposition of the location data by interpolation/extrapolation may
10 also be applied to the TOA case. It is intended that all such modifications come within the spirit and scope of the following claims:

Claims

1. A method for locating a remote unit within a communication system, the method comprising the steps of:
 - 5 receiving a plurality of measurements from a remote unit of Observed Time Differences (OTDs) for a plurality of base stations, wherein the plurality of OTD measurements were performed at a first time period;
receiving a measurement of Real Time Differences (RTD) for the plurality of base stations performed at a second time period;
 - 10 calculating a predicted RTD for the plurality of base stations at the first time period; and
calculating a location of the remote unit based on the OTD measurements and the predicted RTD for the plurality of base stations at the first time period.
- 15 2. The method of claim 1 wherein the step of receiving the plurality of measurements from the remote unit comprises the step of receiving the plurality of measurements from the remote unit of OTDs for the plurality of base stations and a time period when the plurality of OTD measurements were performed.
- 20 3. The method of claim 1 wherein the step of receiving the plurality of measurements from the remote unit comprises the step of receiving the plurality of measurements from the remote unit of OTDs for the plurality of base stations and a frame number when the plurality of OTD measurements were performed.
- 25 4. The method of claim 1 wherein the step of receiving the measurement of RTD for the plurality of base stations comprises the step of receiving the measurement of RTD along with a time period that the RTD measurement was taken.
- 30 5. The method of claim 1 wherein the step of receiving the measurement of RTD for the plurality of base stations comprises the step of receiving the measurement of RTD along with a frame number that the RTD measurement was taken.
6. A method for locating a remote unit within a communication system, the method comprising the steps of:


receiving a radio-frequency (RF) location signal transmitted via a downlink signal;

computing an observed-time-difference (OTD) for each base station at a first time period;

- 5 computing a time period when the location signal was received; and
reporting the OTD measurement along with the time period to infrastructure equipment for locating the remote unit.

7. The method of claim 6 wherein the step of computing the time period when the
10 location signal was received comprises the step of computing a frame when the location signal was received.

8. The method of claim 7 wherein the step of reporting the OTD measurement along with the time period comprises the step of reporting the OTD measurement
15 along with a frame number.






FIG.2

3/3




FIG.3

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US99/08657

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) :H04B 7/005; H04Q 7/20, 7/34

US CL :455/456, 457, 524, 575

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 455/456, 457, 524, 575

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched
NONEElectronic data base consulted during the international search (name of data base and, where practicable, search terms used)
APS

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A,P	US 5,832,381 A (KAUPPI) 03 NOVEMBER 1998	1-8
A	US 5,926,133 A (GREEN Jr.) 20 JULY 1999	1-8
A,P	US 5,809,424 A (EIZENHOEFER) 15 SEPTEMBER 1998	1-8
A	US 5,668,804 A (SUONVIERI) 16 SEPTEMBER 1997	1-8

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

* "A"	document defining the general state of the art which is not considered to be of particular relevance	* "T"	later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
* "E"	earlier document published on or after the international filing date	* "X"	document of particular relevance, the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
* "L"	document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	* "Y"	document of particular relevance, the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
* "U"	document referring to an oral disclosure, use, exhibition or other means	* "&"	document member of the same patent family
* "P"	document published prior to the international filing date but later than the priority date claimed		

Date of the actual completion of the international search

05 AUGUST 1999

Date of mailing of the international search report

10 SEP 1999

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

CONOVER KEAN

Telephone No. (703) 305-4366